

#### Architectural Stone Dressings

Unit 1, The Old Dairy, Bushes Road, Pimperne, Dorset DT11 8US Tel: 01202 739200

E mail: info@broad-stone.co.uk

## Coping Range - January 2022

There are a variety of different designs and sizes to suit most requirements. Where the coping is to be placed may determine the choice of design and width will be gauged by the overall width of the your finished wall - including render if applicable. Where the coping projects from the wall between 35mm and 50mm, all coping units are cast with a drip groove.

If the options below do not meet your requirements, other sizes can be manufactured. Please contact us with your requirements and we will find a solution.


Coping - Flat

Wide	Thickness 'A'
300mm	40mm or 50mm
305mm	50mm
365mm	50mm
380mm	80mm
400mm	50mm
425mm	50mm
450mm	50mm
500mm	50mm
520mm	50mm
600mm	50mm



Most combinations of width and height are possible to manufacture. Flat Coping can be an economic option and be also used as roof coping, on gables as well boundary and garden walls.

Coping - Weathered one way



	Thickness
Wide	'A/B'
200mm	50/75mm
250mm	50/70mm
300mm	50/60mm
320mm	60/80mm
380mm	55/85mm
400mm	50/65mm
400mm	50/80mm
428mm	75/100mm
440mm	50/80mm
475mm	60/85mm
500mm	50/80mm
580mm	50/80mm
600mm	50/75mm

Coping - weathered one way, typically used on boundary and parapet walls. For use on parapet walls, the coping will usually weather 'in' toward the building/flat roof. Thickness 'B', the taller of the two, would be seen from the external elevation.



#### Architectural Stone Dressings

Unit 1, The Old Dairy, Bushes Road, Pimperne, Dorset DT11 8US Tel: 01202 739200 E mail: info@broad-stone.co.uk

# Coping Range - January 2022

Coping - Weathered two ways

Width	Thickness 'A/B'
200mm	50/75mm
280mm	50/90mm
315mm	50/90mm
315mm	70/100mm
320mm	55/80mm
360mm	65/80mm
380mm	50/90mm
400mm	50/90mm
520mm	75/90mm



Coping - weathered two ways, typically used on boundary and garden walls. This design allows rain water to 'run-off' both sides of the wall.

Coping - Weathered two ways, flat top



	Thickness
Width	'A/B'
280mm	60/90mm
280mm	50/100mm
300mm	70/125mm
350mm	70/90mm
360mm	65/95mm
360mm	75/90mm
360mm	90/140mm
400mm	60/90mm
500mm	60/90mm
550mm	65/80mm

Coping weathered two way flat top - Typically used on boundary, parapet/balcony walls where a metal railing or glass balustrade is to be installed. The flat centre section gives an ideal area for placement of posts as needed.



#### Architectural Stone Dressings

Unit 1, The Old Dairy, Bushes Road, Pimperne, Dorset DT11 8US Tel: 01202 739200

E mail: info@broad-stone.co.uk

# Coping Range - January 2016

Call, Email or post enquiries to the Sales Office:

Broad Stone Cast Products Ltd Unit 1, The Old Dairy, Manor Farm Bushes Road Pimperne Dorset DT11 8US Contact:

Tel: 01202 739 200

Email: info@broad-stone.co.uk

### **Bespoke Copings**

We are happy to discuss your special requirements, to match existing coping. Sketches of the coping would be produced for approval prior to manufacture.

### **Deliveries**

When orders are delivered, cast stone units are shrink wrapped on pallets despatched by either flat bed or crane off loading vehicles. If appropriate cast stone can be delivered through a pallet network - across the UK.

Should there be any site access restrictions, please kindly notify the office in advance of any delivery.

### ISO90001:2015

Since January 2022, the company attained ISO9001:2015 Certification. This is our ongoing commitment to providing the best quality and continuous improvement.



Certificate No:387932022